

# 802.11g Wireless PCI Adapter



Complying with the 802.11g standard, the WL-8315 provides a faster wireless connection for desktop users who access network resources. Moreover, the WL-8315 supports specific ways to increase the data transfer rate at a time, compressing the data and decreasing the waiting time to send the next data to the Routers or APs. This feature is called Turbo Mode. When the card is connecting to the Routers or APs with the proprietary Turbo Mode feature, the wireless network will be more effective.

For WLAN security issues, the WL-8315 supports 64/128-Bit WEP data encryption that protects your wireless network from eavesdropping. It also supports WPA (Wi-Fi Protected Access) feature that combines IEEE 802.1x and TKIP (Temporal Key Integrity Protocol) technologies. Client users are required to authorize before accessing to APs or AP Routers, and the data transmitted in the network is encrypted/decrypted by a dynamically changed secret key. Furthermore, this card supports WPA2 function. WPA2 provides a stronger encryption mechanism through AES (Advanced Encryption Standard), which is a requirement for corporate and government users.

The WL-8315 supports WMM. WMM (Wi-Fi Multi-Media) is a new technology that can grant higher priorities to multimedia data traffics, thus meet the bandwidth requirement for special applications.

It supports most operating systems such as Windows98SE/Me/2000/XP/ Server 2003 and offers greater scalability and usability, making the device a perfect choice for users who are getting tired of running cables or in constant need of wireless access

#### **KEY FEATURE**

- IEEE 802.11b/g standard compliant
- Supports Turbo mode to enhance the data transfer speed (the connected AP must support Turbo mode as well)
- Supports WMM (WiFi Multi-Media) function to meet the multimedia data bandwidth requirement (the connected AP and the application must support WMM as well)
- Utilization of Direct Sequence Spread Spectrum plus OFDM modulation to provide a robust, interference-resistant solution in a multi-user environment
- Supports Ad-Hoc / Infrastructure
- Supports of most popular operating systems including
  Windows 98SF/Me/2000/XP and Server 2003
- Supports Power Save mode

**Data Sheet** 



## **SPECIFICATION**

**Product** 

Model	WL-8315
Interface	Complaint with PCI 2.2 standard
Standards Conformance	Compliant with 802.11b/802.11g
Data Transfer Rate	11b: 1/2/5.5/11Mbps (auto sensing)
	11g: 6/9/12/18/24/36/48/54Mbps (auto sensing
Operating Mode	Infrastructure Mode, Ad-Hoc Mode
Security	WEP 64/128Bit, WPA, WPA2
RF Modulation	11g: OFDM with BPSK, QPSK, 16-QAM, 64QAM
	11b: BPSK, QPSK, CCK
Media Access Protocol	CSMA/CA
Output Power	18dBm (Max.)
LED Indicators	ACT, LNK
Operating systems	Windows 98/Me/2000/XP/Server 2003

802.11g Wireless PCI Adapter

Environmental	& Mechanical	Characteristics

Temperature	Operating: 0 ~ 55 Degree C
	Storage: -20 ~ 70 Degree C

	5
Operating Humidity	Operating: 10% to 90% Non-Condensing
	Storage: 5% to 95% Non-Condensing

	Storage: 5% to 95% Non-Condensing
Dimensions (L x W x H)	134.5 x 121 x 21mm
Weight	54g
Certifications	FCC. CE

### **APPLICATIONS**

### Infrastructure

For some environments with limitations on running Ethernet cables around, simply install the WL-8315 on your desktop or laptop, and users thus can get connected to the wired Ethernet through a wireless access point to access the network resources within the coverage of wireless signals. The installation of multiple access points to enlarge the coverage of wireless signals and can ensure seamless network access for mobile users.



#### Ad-Hoc

Need connecting several desktop PC or notebooks wirelessly? Configuring all the wireless adapters to Ad-Hoc mode without wireless access point is the easiest and costly way to meet this demand.



## ORDERING INFORMATION

WL-8315 802.11g Wireless PCI Adapter